

實體設計 Creo Parametric 4.0 & SolidWorks 2016 與 Creo Parametric 2.0 & SolidWorks 2014
 答案與公差範圍異動表

題號	版本	答案 公差	1	2	3	4	5
106	Creo Parametric 4.0 & SolidWorks 2016	Ans	50.9502	334162.7905	53.1139	351652.3019	38489.0839
		Tol	±0.01	±19	±0.01	±30	±3
	Creo Parametric 2.0 & SolidWorks 2014	Ans	50.9502	334162.7905	53.1139	351652.3019	38489.0839
		Tol	±0.01	±14.3	±0.01	±30	±3
302	Creo Parametric 4.0 & SolidWorks 2016	Ans	117.4677	7015808.799	117.5696	7149820.966	483246.0985
		Tol	±0.05	±40	±0.005	±42	±5
	Creo Parametric 2.0 & SolidWorks 2014	Ans	117.4677	7015808.799	117.5696	7149820.966	483246.0985
		Tol	±0.05	±15	±0.005	±15	±5
310	Creo Parametric 4.0 & SolidWorks 2016	Ans	25.1664	1453.2072	23.7522	1259.1549	3455.2637
		Tol	±0.01	±0.07	±0.05	±0.3	±0.7
	Creo Parametric 2.0 & SolidWorks 2014	Ans	25.1664	1453.2072	23.7522	1259.1549	3455.2637
		Tol	±0.01	±0.05	±0.002	±0.04	±0.04

題號	版本	答案 公差	1	2	3	4	5
503	Creo Parametric 4.0 & SolidWorks 2016	Ans	0.0687	1.3522	0.5237	0.0709	1.3656
		Tol	±0.005	±0.02	±0.003	±0.005	±0.1
	Creo Parametric 2.0 & SolidWorks 2014	Ans	0.0687	1.3522	0.5237	0.0709	1.3656
		Tol	±0.005	±0.02	±0.003	±0.005	±0.02

註：Creo Parametric 4.0 & SolidWorks 2016，題目 405 停用。本題已不列入認證考題範圍，僅供讀者自我練習提昇能力。